





SPECIFICATIONS

KEY COMPONENTS	LX.6+2	LX.6+2 XRT	MODELS
SYSTEM	Electric 48V A	C Drive System	
MOTOR	5KW 48V AC Asynchronous Motor		
CONTROLLER	450A Speed Controller		
TRANSAXLE	Single Speed With 16:1 Gear Ratio		
CHARGER	RoyPow 20A Automatic Charger		
DC-DC CONVERTER		DC-DC 48V-12V 300W	,

PERFORMANCE	LX.6+2	LX.6+2 XRT MODELS	
STEERING	Two Way Rac	k & Pinion	
FRONT SUSPENSION	McPherson In	dependent Lifted Front Suspension.	
	Helical Spring	With Hydraulic Shock Absorption.	
REAR SUSPENSION	Integral Type	Transaxle. Helical Spring With Shock	
	Absorption. Re	ear Stabiliser Bar.	
BRAKES	4 Wheel Hydraulic Disc Brakes		
PARK BRAKE	Electro-Magne	Electro-Magnetic Parking Brake	
BODY PANELS	Automotive Grade Injection Moulded PP Material		
PAINT FINISH	Premium Painted Base Or Metallic Colours.		
TYRES	20x10-10" Su	per Turf Tyres	
SPORT MODE SPEED	35km/h		
ECO MODE SPEED	25km/h		
CURB WEIGHT	540kg	558kg	
MIN TURNING RADIUS	5.8m	.1	
BRAKING DISTANCE	≤ 6m		

DIMENSIONS	LX.6+2	LX.6+2 XRT	MODELS
OVERALL DIMENSIONS	4405 mm x 1210mi	m x 1915mm (Lx\	VxH)
MIN GROUND CLEARANCE	120 mm		
	3260 mm		

BATTERY	LX.6+2	LX.6+2 XRT MODE	
TYPE	RoyPow Lithium LiFePO4		
MODEL	S51105P	S51150P	
STORED ENERGY	5.3KW/h	7.68KW/h	
MAXIMUM DISCHARGE	315A (30s)	315A (30s)	
CONTINUOUS DISCHARGE	200A	180A	
AVERAGE RANGE	55-65km (3 Rounds)	90-100km (4-5 rounds)	

KEY FEATURES



Additional Base Model Features include:

LED Headlights + Taillights - Flickers - Warning Lights - Speedometer - Dual USB Charging Ports - Non-Universal Key Switch - Premium Steering Wheel - Hooter - Corrugated Aluminium Floor - Battery Level Indicator - Extended Roof Canopy - Reverse Buzzer - Fully Foldable Rear Seat - 10" Super Turf Tyres and Rims

Optional Accessories include: Glass Windshield With Wiper - Cerwin Vega Bluetooth SoundBar - Custom Marine Vinyl Seats - Weather Enclosure - Custom Colour Panels - Canvas Storage Cover. Enquire For More Info On Optional Accessories.

*Specifications & features may change as the model is developed.

